



# SEA-SHIELD

PREMIUM YACHT PRODUCTS

Sea-Shield Inc.  
6110 33rd Street East  
Brandenton FL 34203  
info@sea-shield.com  
www.sea-shield.com

## Exhaust Guard™

Synthetic Hydrophobic Wax



Part	Size	Case Size
SEA-RSR16	16 OZ	12
SEA-RSR1	1 Gallon	4

### BENEFITS

- \* Protects against engine exhaust and black streaks
- \* Lasts months with a single coating
- \* Fast and easy application
- \* Seals and protects paint, gelcoat, hypalon, rubber and plastics

### DESCRIPTION

This product is a powerful polymer-based surface sealant designed to seal and protect finishes from black streaks, engine exhaust, industrial fallout, acid rain, saltwater and UV rays. It seals and protects paint, gel coat, hypalon, rubber and hard plastic surfaces.

### DIRECTIONS

Apply sealant to a clean, buffed or well-prepared surface.

Use a small amount on an applicator and wipe until surface is thoroughly covered, then wipe off excess with a clean microfiber towel. This product can also be applied using a Random Orbital with a Sea-Shield® Black Sealing Pad or other soft sealing pad. Product becomes fully cured in 24 hours but can get wet within an hour. However, for best results, wait 8 hours before getting surface wet.

### RECOMEND SURFACE

- Paint
- Gelcoat



Clean

Polish

Protect